

PROTEK™

PROTEK MPL-1 (Multi purpose lubricant) MATERIAL SAFETY DATA SHEET

Protek Products Inc. NY
P.O. Box 385
Smithtown New York 11787

Identity: Fluoropolymeric suspension in petrolatum.

Hazardous components/Identity information

Hazardous components	OSHA PEL	ACGIH TVL	OTHER	PERCENT
----------------------	----------	-----------	-------	---------

NONE

Physical and Chemical characteristics

Boiling Point	N/A
Vapor Pressure	(68 deg F.) <1
Vapor Density	(Air=1.0) ND
Solubility in Water	Insoluble
Specific Gravity	(2HO=1) 0.76-0.87 @60C
Volatile by Volume	N/A
VOC Content	N/A
Appearance	Semi Solid
Odor	No Odor

Fire and Explosion Hazard Data

Flash Point: 425 Deg F

Method used: ASFM D-92

Extinguishing Media: CO2, Dry Chemical, Foam



Reactivity Data

Stability: MPL-1 is stable

Incompatibility: Avoid mixing with caustic soda, potash or oxidizing materials.

Hazard Information

Eyes: Very mild eye irritant.

Skin: Non irritating

Ingestion: Could cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Inhalation: Gross over inhalation may cause symptoms such as, coughing, May aggravate pre-existing lung disorders.

Carcinogenicity: NTP-No, IARC monograph-No OSHA regulated-No

IMPORTANT NOTICE

The information presented herein is believed to be accurate, however, NO WARRANTY of any kind, either expressed or implied, is made regarding the product described herein or the information or recommendations contained herein. Since the conditions of use, handling and storage of this product are not in Protek Products Inc. control. Protek Products Inc. assumes no liability or responsibility with respect to personal injury or property damage resulting there from or with respect to results obtained from the use of Protek MPL-1.