

OLI-CELL Polier-und Schwabbellack 4.74

OLI-CELL Polishing and buffing lacquer 4.74

Product description

Buffable, excellently filling, cellulose-based priming and finishing lacquer for high-gloss, closed-pore wooden surfaces in the interior.

Properties

-polishable and buffable -rich in solids
 -highly transparent -good scratch resistance and water repellence -good sanding properties -smooth and good bonding

Areas of application

Particularly suitable for the high-gloss, closed-pore surface coating of exotic woods, but also for all conventional wood types and woodwork in the interior, such as furniture, interior fittings and music instruments.

Test standards

-DIN EN 71-3 (heavy metals) -DIN 53160 (sweat and saliva resistant)
 -DIN 68861 T1 B (certain surfaces)
 -DIN 68861 T1 C (chemical resistance) -hand cream resistant
 -free of APEO -free of formaldehyde
 -DINP-free

Ordering information

Gloss levels high gloss 200 / 331 612 00 913 625 02
 Container 30 ltrs V 21
 sizes Thinner

For labelling details and safety instructions, please refer to our safety datasheet at www.oli-lacke.de.

Technical data

Shelf-life in factory sealed containers: 12 months
 Thinner: V 21 Curing agent: -Mixing ratio: Air
 drying at +23°C/65% rh Dust dry: 40 min Sandable
 and buffable: 4 days Stackable:

Methods of application



Gloss levels high gloss 200 / 331 612 00 913 625 02
 Container 30 ltrs V 21
 sizes Thinner

Labelling

Thinner 40-50% Viscosity DIN 4mm 30-40% 25-30
 20-25 sec Spray pressure (bar) sec 100-150
 0,23-0,28
 80-120
 The surface must be absolutely dry and free of dirt, oil, grease and sanding dust.
 Coverage (g/sqm) 80-120

Application


Example:

music instrument: cello, spruce, high-gloss



Gradual sanding: grit size 180-220
 Staining: OLI-AQUA Wood stain Brillant 0401,
 50 g/sqm

Air drying: 5-6 hrs
 Lacquering: OLI-CELL Polishing and buffing lacquer,
 2 spray coats 'wet in wet', 100 g/sqm each
 over night



Intermediate sanding: grit size 240-280
 Patination: OLI-AQUA Wood stain Rustic 0401,
 30-40 g/sqm

Air drying: 30 min
 Lacquering: OLI-CELL Polishing and buffing lacquer,
 100 g/sqm
 Air drying: over night
 Top coat: OLI-CELL Polishing and buffing lacquer,
 100 g/sqm
 Air drying: 3 days